

## DECLARAÇÃO DE DESEMPENHO

### 002DDGP

**1 – Código de identificação único do produto / tipo:**

Ladrilhos cerâmicos prensados a seco, GL ou UGL, com absorção de água inferior ou igual a 0.5% ( $E_b \leq 0.5\%$ )

**2 – Utilização:**

Revestimentos de chão e/ou paredes, interiores ou exteriores

**3 – Nome e endereço do fabricante:**

Revigrés, Indústria de Revestimentos de Grés, Lda.

Apartado 1

3754-001 Barrô (Águeda)

Portugal

[www.revigres.com](http://www.revigres.com)

**4 – Sistema de avaliação e verificação da regularidade do desempenho aplicável:**

Sistema 4

**5 – Desempenho declarado:**

<u>Características essenciais</u>	<u>Desempenho</u>	<u>Norma harmonizada</u>
<b>Reacção ao fogo</b>	A1 e A1 <sub>FL</sub>	EN 14411:2012 (Grupo B1a GL ou UGL)
<b>Libertação de substâncias perigosas:</b> - Cádmio (Cd) - Chumbo (Pb)	NPD NPD	
<b>Resistência à Flexão:</b> - Espessura < 7,5mm ≥ 7,5mm	> 1500 N > 2000 N	
<b>Resistência à colagem / aderência</b>	NPD	
<b>Escorregamento</b>	NPD	
<b>Resistência ao choque térmico</b>	Cumpre	
<b>Tactilidade:</b>	NPD	
<b>Durabilidade, para:</b> - Uso interno - Uso externo (resistência ao gelo)	Cumpre Cumpre	

NPD – Desempenho não declarado. Declarado, caso a caso, a pedido do cliente.

Esta declaração de desempenho foi emitida sob a inteira responsabilidade do fabricante, identificado no ponto 3.

Departamento Qualidade

Rui Vasco  
27.06.2014

## PERFORMANCE STATEMENT

### 002DDGP

#### 1 –Unique identification code for product / type:

Glazed or unglazed dry pressed ceramic tiles, with water absorption less than 0.5% ( $E_b \leq 0.5\%$ ).

#### 2 – Use:

For internal or external, floor and wall.

#### 3 –Name and address of manufacturer:

Revigrés, Indústria de Revestimentos de Grés, Lda.  
Apartado 1  
3754-001 Barrô (Águeda)  
Portugal

#### 4 –System of assessment and checking for regularity of applicable performance:

System 4

#### 5 – Performance declared:

<u>Essential characteristics</u>	<u>Performance</u>	<u>Standard</u>
<b>Reaction to fire</b>	A1 and A1 <sub>FL</sub>	EN 14411:2012 (Group Bla GL or UGL)
<b>Release of dangerous substances, for:</b> - Cadmium (Cd) - Lead (Pb)	NPD NPD	
<b>Bending strength:</b> - Thickness < 7,5mm ≥ 7,5mm	> 1500 N > 2000 N	
<b>Bond strenght/adhesion, for:</b>	NPD	
<b>Slippage</b>	NPD	
<b>Resistance to thermal shock</b>	Resistant	
<b>Tactility:</b>	NPD	
<b>Durability, for:</b> - Internal use - External use (resistance to frost)	Compliant Compliant	

NPD – Non Stated Performance. It is stated for each case, on client's request.

This performance statement has been issued under the responsibility of the manufacturer identified in point 3.

Quality Department



Rui Vasco  
27.06.2014